



Product: Shock Pack Lanyard
Part#: 5256-01-01

SPECIFICATIONS
 PAGE 1 OF 1



| PRODUCT FEATURES | |
|---------------------------|---------|
| Legs | 2 |
| Length | 4.5'-6' |
| Hook Type | Rebar |
| Available D-Ring Extender | Yes |
| Tie Back Capable | Yes |

| MATERIAL SPECIFICATIONS | | |
|-------------------------|---------------------|----------------|
| Item | Description | Break Strength |
| Webbing | 1" Polyester | 9,800 LBS |
| Shock Pack Webbing | 2" Polyester | 6,000 LBS |
| Snap Hooks | Forged Plated Steel | 5,000 LBS |

| TECHNICAL SPECIFICATIONS | |
|----------------------------|---------------------------------|
| Item Weight | 5 LBS |
| Worker Weight Limit | 310 LBS |
| Max Free Fall | 6' |
| Max Arrest Force 310 LBS | 1150 LBS |
| Avg Arrest Force 310 LBS | <900 LBS |
| Maximum Elongation 310 LBS | 42" |
| Compliance References | OSHA 1910, 1926, ANSI Z359-2009 |
| Testing Reference | ANSI Z359.13-2009 |

Manufactured by Safe Approach, Inc., 206 Mechanic Falls Rd., Poland, ME 04274
 (800) 471-1157, Fax (207) 345-9100, www.safeapproach.com