



Product: Shock Pack Lanyard
Part#: 5306-01-01

SPECIFICATIONS
 PAGE 1 OF 1



| PRODUCT FEATURES | |
|---------------------------|----------|
| Legs | 1 |
| Length | 6' |
| Hook Type | Standard |
| Available D-Ring Extender | Yes |
| Tie Back Capable | No |

| MATERIAL SPECIFICATIONS | | |
|-------------------------|---------------------|----------------|
| Item | Description | Break Strength |
| Webbing | 1" Polyester | 9,800 LBS |
| Shock Pack Webbing | 2" Polyester | 6,000 LBS |
| Snap Hooks | Forged Plated Steel | 5,000 LBS |

| TECHNICAL SPECIFICATIONS | |
|--------------------------------|------------------------------------|
| Item Weight | 3 LBS |
| Worker Weight Limit | 310 LBS—12' Fall (400 LBS—6' Fall) |
| Max Free Fall | 12' |
| Max Arrest Force 12' 310 LBS | 1350 LBS |
| Avg Arrest Force 12' 310 LBS | <900 LBS |
| Maximum Elongation 12' 310 LBS | 48" |
| Max Arrest Force 6' 400 LBS | 1350 LBS |
| Avg Arrest Force 6' 400 LBS | <900 LBS |
| Maximum Elongation 6' 400 LBS | 60" |
| Compliance References | OSHA 1910, 1926, ANSI Z359-2009 |
| Testing Reference | ANSI Z359.13-2009 |

Manufactured by Safe Approach, Inc., 206 Mechanic Falls Rd., Poland, ME 04274
 (800) 471-1157, Fax (207) 345-9100, www.safeapproach.com