

Self Retracting Lifeline Part#: See Below



Part Number	Configuration	Connector	Hook
2156-01-01	Single	Steel Carabiner	Steel Snap
2156-11-11	Single	Alum Carabiner	Alum Snap
2156-11-12	Single	Alum Carabiner	Alum Rebar
2256-01-01	Double	Steel Carabiner	Steel Snap
2256-11-11	Double	Alum Carabiner	Alum Snap
2256-11-12	Double	Alum Carabiner	Alum Rebar

DESCRIPTION

The self retracting lifeline from Safe Approach features heavy duty 3/4" Technora webbing and a lightweight rugged cast poly housing. This SRL is fully serviceable for a longer life. This unit also meets all OSHA and ANSI requirements for foot level tie-off and for work above the connection point up to a maximum free fall of 5".

GENERAL SPECIFICATIONS

Item Description

Housing Thermoplastic Webbing 3/4" Technora

Working Length 6'

Hooks Alloy Steel or Aluminum

Eye Steel, Swiveling

Capacity: 310 lbs—overhead or foot level tie-off

420 lbs—overhead tie-off

Max Arrest Force: 900 lbs Static Load: 4,500 lbs Max Arrest Distance: <54"

Technical References: Meets OSHA 1910, 1926, ANSI Z359 2.58 / 3.2.8 /

4.3.7 / 4.3.8, ANSI Z359.14 Class B

Testing References: ANSI Z 359 4.3.7.1 through 4.3.7.4